



Lighting Your Savings
Lighting Your Success

Product

Data Sheet

ES-LDL01-15016W-CCT

Features

- Triac dimmable
- CCT selectable: 3000K, 4000K, 6000K
- Polyamide body with latest heat dissipation technology
- High efficiency SMD LED chips 90lm/w
- IC-4
- CRI ≥ 80 and good stability over lifetime
- Quick and simple installation, with flex and plug
- IP44 below ceiling, IP20 within the ceiling space
- 5-year warranty



Standards

- IEC/AS/NZS 60598.1
- IEC/AS/NZS 60598.2.1
- IEC/AS/NZS 60598.2.2
- IEC/AS/NZS CISPR 15

Specifications

MODEL	ES-LDL01-15016W-CCT	HOUSING COLOUR	White
INPUT VOLTAGE(V)	220-240	MATERIAL	Conduction material+aluminum
PROTECTION CLASS	II	OPERATING TEMPERATURE(°C)	-20°C~+40°C
POWER FACTOR(PF)	0.9	DIMMABLE(Y/N)	YES
WATTAGE(W)	16	IC-4(Y/N)	YES
LUMEN OUTPUT(LM)	1440	INSTALLATION TYPE	RECESSED
EFFLICACY(LM/W)	90	DIMENSION(mm)	Ø190*80
BEAM ANGLE(°)	120	CUT OUT	Ø150
COLOUR TEMPERATURE(K)	Tricolour:3000-4000-6000	NET WEIGHT(kg)	0.4
IP	44	LIFE SPAN	50000 HOURS
CRI(Ra)	>80	WARRANTY	5 YEARS
SDCM	<5	COMPLIANCE	GMA,RCM