



Lighting Your Savings
Lighting Your Success

Product

Data Sheet

TL-DL01-7007W-CCT

Features

- Triac dimmable
- CCT selectable: 3000K, 4000K, 6000K
- Polyamide body with latest heat dissipation technology
- High efficiency SMD LED chips 100lm/w
- IC-4
- CRI ≥ 80 and good stability over lifetime
- Quick and simple installation, with flex and plug
- IP44 below ceiling, IP40 within the ceiling space
- 3-year warranty



Standards

- IEC/AS/NZS 60598.1
- IEC/AS/NZS 60598.2.1
- IEC/AS/NZS 60598.2.2
- IEC/AS/NZS CISPR 15

Specifications

MODEL	TL-DL01-7007W-CCT	HOUSING COLOUR	White
INPUT VOLTAGE(V)	220-240	MATERIAL	Conduction material+aluminum
PROTECTION CLASS	II	OPERATING TEMPERATURE(°C)	-20°C~+45°C
POWER FACTOR(PF)	0.9	DIMMABLE(Y/N)	YES
WATTAGE(W)	7	IC-4 (Y/N)	YES
LUMEN OUTPUT(LM)	700	INSTALLATION TYPE	RECESSED
EFFLICACY(LM/W)	100	DIMENSION (mm)	Ø92*55
BEAM ANGLE	120°	CUT OUT	Ø70
COLOUR TEMPERATURE(K)	Tricolour:3000-4000-6000	NET WEIGHT (kg)	0.2
IP	44	LIFE SPAN	30000 HOURS
CRI(Ra)	>80	WARRANTY	3 YEARS
SDCM	<5	COMPLIANCE	SAA, RCM