



Lighting Your Savings
Lighting Your Success

Product

Data Sheet

TL-DL02-9010W-CCT-5Y

Features

- Triac dimmable
- CCT selectable: 3000K, 4000K, 6000K
- Polyamide body with latest heat dissipation technology
- High efficiency SMD LED chips 100lm/w
- IC-4
- CRI ≥ 80 and good stability over lifetime
- Quick and simple installation, with flex and plug
- IP44 below ceiling, IP40 within the ceiling space
- 5-year warranty



Standards

- IEC/AS/NZS 60598.1
- IEC/AS/NZS 60598.2.1
- IEC/AS/NZS 60598.2.2
- IEC/AS/NZS CISPR 15

Specifications

MODEL	TL-DL02-9010W-CCT-5Y	HOUSING COLOUR	White
INPUT VOLTAGE(V)	220-240	MATERIAL	Conduction material+aluminum
PROTECTION CLASS	II	OPERATING TEMPERATURE(°C)	-20°C~+45°C
POWER FACTOR(PF)	0.9	DIMMABLE(Y/N)	YES
WATTAGE(W)	10	IC-4(Y/N)	YES
LUMEN OUTPUT(LM)	1000	INSTALLATION TYPE	RECESSED
EFFLICACY(LM/W)	100	DIMENSION(mm)	Ø115*60
BEAM ANGLE(°)	120	CUT OUT	Ø90
COLOUR TEMPERATURE(K)	Tricolour:3000-4000-6000	NET WEIGHT(kg)	0.23
IP	44	LIFE SPAN	50000 HOURS
CRI(Ra)	>80	WARRANTY	5 YEARS
SDCM	<5	COMPLIANCE	SAA,RCM