



Lighting Your Savings
Lighting Your Success

Product

Data Sheet

ES-PL01-6060-36W-CCT

Features

- Tricolor Technology: Switch between 3000K,4000K, 6000K
- Efficient Backlit Design: The backlit design ensures uniform light distribution, eliminating uneven brightness.
- Energy Efficiency: With a power factor of 0.9 and an efficacy of 90 LM/W, the panel light offers efficient lighting while reducing energy consumption.
- Wide Beam Angle: The 120° beam angle provides expansive and consistent illumination, enhancing visual comfort.
- 3-year warranty



Standards

- AS/NZS 60598.1
- AS/NZS 60598.2.1
- AS CISPR 15

Specifications

MODEL	ES-PL01-6060-36W-CCT	HOUSING COLOUR	White
INPUT VOLTAGE(V)	220-240	MATERIAL	Aluminium+Polycarbonate
PROTECTION CLASS	II	OPERATING TEMPERATURE(°C)	-20°C~+45°C
POWER FACTOR(PF)	0.9	DIMMABLE(Y/N)	NO
WATTAGE(W)	36	UGR	21
LUMEN OUTPUT(LM)	3240	INSTALLATION TYPE	Ceiling Mount
EFFLICACY(LM/W)	90	DIMENSION(mm)	600*600*35
BEAM ANGLE(°)	120	IK	N/A
COLOUR TEMPERATURE(K)	Tricolour:3000-4000-6000	NET WEIGHT(kg)	1.91
IP	20	LIFE SPAN	30000 HOURS
CRI(Ra)	80	WARRANTY	3 YEARS
SDCM	<6	COMPLIANCE	GMA,RCM