

lighting Your Savings ng Your Success

Product

Data Sheet

ES-TL01-32W 3000K-BK 4000K-WH

Features

- The 24° beam angle provides directed and precise lighting for various applications
- High CRI of 90 ensures accurate color representation
- An efficacy of 90 lumens per watt offers both energy efficiency and brightness.
- The light can be rotated up to 350° and adjusted vertically up to 90°, allowing for customized lighting angles
- Operates reliably in a temperature range of -20°C to +45°C
- The aluminum material helps dissipate heat effectively for consistent performance
- 3-year warranty

Standards

- IEC/AS/NZS 60598.1
- IEC/AS/NZS 60598.2.1
- AS CISPR 15





Specifications

MODEL	ES-TL01-32W	HOUSING COLOUR	Black Or White
INPUT VOLTAGE(V)	220-240	MATERIAL	Aluminum
PROTECTION CLASS	I	OPERATING TEMPERATURE(°C)	-20°C~+45°C
POWER FACTOR(PF)	0.9	DIMMABLE(Y/N)	NO
WATTAGE(W)	32	ADJUSTABLE ANGEL (°)	90°Vertical, 350°Rotation
LUMEN OUTPUT(LM)	2880	INSTALLATION TYPE	Universal 1 circuit track
EFFLICACY(LM/W)	90	DIMENSION(mm)	Ø90*150
BEAM ANGLE(°)	24°	NET WEIGHT(kg)	0.94 (without track)
COLOUR TEMPERATURE(K)	3000 in Black,4000 in White	LIFE SPAN	30000 HOURS
IP	20	WARRANTY	3 YEARS
CRI(Ra)	90	COMPLIANCE	GMA,RCM

