



*Lighting Your Savings*  
*Lighting Your Success*

**Product**

Data Sheet

## TL-SSWL01-13W-6000K

### Features

- Durable Polycarbonate: Crafted from robust polycarbonate material, offering both longevity and resilience.
- Temperature Resilience: Operating smoothly within a temperature range of -20°C to +45°C and is suitable for diverse environments and conditions.
- Enhanced Brightness: Emitting a total of 1300 lumens, enhancing your space with brilliant lighting.
- 3-year warranty



### Standards

- AS/NZS 60598.1
- AS/NZS 60598.2.1
- AS CISPR 15

### Specifications

MODEL	TL-SSWL01-13W-6000K	HOUSING COLOUR	Black
INPUT VOLTAGE(V)	220-240	MATERIAL	Polycarbonate
POWER FACTOR(PF)	0.9	OPERATING TEMPERATURE(°C)	-20°C~+45°C
WATTAGE(W)	13	DIMMABLE(Y/N)	NO
LUMEN OUTPUT(LM)	1300	INSTALLATION TYPE	Wall & Surface mount
EFFLICACY(LM/W)	100	DIMENSION(mm)	L168*H181
BEAM ANGLE(°)	120	NET WEIGHT(kg)	0.5
COLOUR TEMPERATURE(K)	6000	LIFE SPAN	30000 HOURS
IP	54	WARRANTY	3 YEARS
CRI(Ra)	90	COMPLIANCE	SAA,RCM