



*Lighting Your Savings
Lighting Your Success*

Product

Data Sheet

ALL-IN-ONE EASY CONNECT EXIT

CODE: EXLEDL



**E&E LIGHTING
AUSTRALIA**



White finish



Black finish

CODE	DESCRIPTION
EXLEDL	All-in-One Easy Connect Exit
EXLEDLBK	All-in-One Easy Connect Exit - Black Finish

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	1.5kg (unit) - 7.5kg (box)
Dimension (L x W x H)	355mm x 80mm x 215mm

OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 E2 C90 E2
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BLEDL	LiFePO4 Lithium Battery, 3.2V 1600mAh

Warranty

3 Years

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m	
E2	5.0	5.2	5.2	5.2	5.2	0.0	0.0	0.0	0.0	N/A

