



*Lighting Your Savings
Lighting Your Success*

Product
Data Sheet

ALL-IN-ONE SURFACE MOUNT EXIT EXWAY



PRODUCT	DESCRIPTION
CODE EXWAY	All-in-OneSurface Mount Exit
EXWAY-ST	All-in-OneSurface Mount Exit - Self Test

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	1.2kg (unit) - 6.0kg (box)
Dimension (L x W x H)	365mm x 80mm x 230mm



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
Temperature	IP20
IP Rating	Large Terminal Block
Wiring	Wall or Ceiling Surface Mount
Mountain Type	Manual Test Switch
Testing System	Polycarbonate Body and Diffuser
Construction	C0 D8 C90 D6.3
Classification	AS/NZ 2293
Standards	AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART	DESCRIPTION
NUMBER	LiFePO4 Lithium Battery, 3.2V 1500mAh
BWAY	
Warranty	3 Years

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATIO	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
N D8	9.	9.	9.	10.	10.	10.	10.	10.	10.
D6.3	4	7	9	1	2	3	3	3	1
	8.	8.	8.	9.1	9.1	9.2	9.1	9.0	8.7
	5	8	9						

